

ROKOAT LVT

Overview

Rokoat LVT is a bespoke formulated Leather and Vinyl protector ideal for use on tenders, yachts, aircraft, vehicles, furniture and clothing. An all-round product, which provides a protective non-greasy yet ultra-shiny smooth finish, Rokoat LVT does not affect the colour of the surface it is applied on. Rokoat LVT nourishes and penetrates deep into the surface of any leather or vinyl surface. It cleans as it is applied, softening and creating a barrier, which gives long lasting protection from stains, blemishes and UV discolouration.

Features



- All-in-one coating, nourishes and protects leather and vinyl.
- Out performs lacquers, waxes and creams.
- Creates a microscopic physical barrier against staining & UV.
- Reduces cleaning and maintenance time and money.
- Non-greasy, slippery or shiny – restores the natural look and feel.

Applicable Surfaces



Typical Applications: All leather and vinyl surfaces.

- Leather
- Vinyl
- Vehicle Interiors
- Yacht Interiors
- Yacht Tenders
- Aircraft Interiors
- Furniture (including faux leather)
- Boots
- Bags
- Jackets

* Not applicable for Suede.

Properties

Colour	Cream
Seconds #2 Zahn	N/A
Percent of Solids	TBA
Odour (liquid)	Slight Solvent
Odour (cured)	None
V.O.C.	Exempt per CFR 51.1 / Reg 8
Coefficient of Friction	N/A
Thermal Stability (cured)	N/A
Conical Bond (1.27 cm mandrel)	N/A
Adhesion	N/A
Impact Direct	N/A
Specific Gravity	N/A
Average Dry film thickness	N/A
Estimated Coverage Rate	20 m ² per Litre
Cure time	5-15 min
RoHS	Compliant
Halogens	None
Pencil Hardness	N/A

Application Methods & Storage Considerations



WIPE

- Shake the bottle well before use.
- Can be used in direct sunlight.
- Ensure the surface is clean and dry
- Apply a modest amount of Rokoat LVT to a lint free cloth or micro-fibre.
- Using a swirling motion, apply the product onto the surface.
- Allow to dry - 3-10 minutes depending on temperature / sunlight conditions.
- Buff if required.
- Can be stored for up to 12 months in original unopened container.
- Store away from heat and sunlight.
- Should not cause skin or eye irritation, however if irritation occurs flush area with clear water.
- We recommend with any application of nano coatings, protective gloves that are worn.
- Further information can be found in the ProductMaterial Safety Data Sheet (MSDS).
- Visit rokoat.com for further information.