

ROKOAT RPX 3000 MarineOne

Overview

ROKOAT RPX 3000 MarineOne is revolutionising the ceramic coating industry for yachts and power boats. Providing chemical & scratch resistance, corrosion protection and a super-smooth glass like non-stick surface, it has been specifically developed by ROKOAT's laboratories to withstand extreme corrosive and abrasive conditions that can quickly destroy conventional paint protective coatings. Designed as a 'once a year' coating and competitively priced, RPX3000 is easy to use and can be applied to both paint & Gelcoat. ROKOAT RPX 3000 MarineOne is weather, UV, chemical, salt and abrasion resistant.

Features



- The super slick glass like surface.
- Designed especially for the luxury yacht industry
- UV, weather, chemical, salt and abrasion resistant.
- Extreme adhesion to substrate, adhering to almost any clean paint surface.
- Paint & Gelcoat compatible.
- Provides ultra-durable surface.
- Incredible 1µm thickness.
- Contains no zinc, lead or chromates.
- Resists soot, staining, salt water & grime.
- Easy to clean.
- 1 year of protection.
- 9H hardness

Applicable Surfaces



All types of painted yachts and boats. Paint & Gelcoat. Can be applied to varnished wood tables & furniture for similar protective results.

Properties

Colour	Clear
Viscosity	TBA
Percent of Solids	TBA
Odour (liquid)	Slight Solvent
Odour (cured)	NONE
V.O.C.	TBA
RoHS	TBA
Coefficient of Friction	TBA
Thermal Stability (cured)	TBA
Conical Bond	TBA
Pencil Hardness	TBA
Cross cut adhesion	TBA
Specific Gravity	TBA
Average applied dry film thickness	1µm
Estimated Coverage Rate @1µm	30m2 per 250mL
Transfer to surrounding material	TBA
Dust free (time @ambient)	TBA
Semi-cured (time-ambient)	TBA
Full Cure Time (ambient)	TBA
Re-coat (or to apply stickers, decals)	Requires ROKOAT TechShield Bonding Primer
Cleaning	TBA

Application Methods & Storage Considerations



WIPE

- Professional Application only.
- Detailed application methods can be found in the Product Application Guide.
- Use in well ventilated areas.
- Do not use in direct sunlight.
- Clean and prepare carefully the surface to be treated.
- Use vapour filters on a mask.
- This product has extreme adhesion properties and requires high abrasion for removal. Ensure surfaces that are not to be coated are well protected.
- Should not cause skin or eye irritation, however if irritation occurs flush area with clear water **
- Can be stored for up to 12 months in original unopened container.
- Store away from heat and sunlight.
- Further information can be found in the ProductMaterial Safety Data Sheet (MSDS).
- Visit rokoat.com for further information.